

# Package: highs (via r-universe)

June 8, 2026

**Type** Package

**Title** 'HiGHS' Optimization Solver

**Version** 1.12.0-3

**Description** R interface to 'HiGHS', an optimization solver for solving mixed integer optimization problems with quadratic or linear objective and linear constraints.

**License** GPL (>= 2)

**Imports** Rcpp (>= 1.0.7), checkmate

**Depends** R (>= 4.0.0)

**SystemRequirements** Bash, PkgConfig, CMAKE (>=3.16), C++17

**URL** <https://gitlab.com/roigrp/solver/highs>

**BugReports** <https://gitlab.com/roigrp/solver/highs/-/issues>

**Suggests** tinytest

**Biarch** FALSE

**LinkingTo** Rcpp

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**NeedsCompilation** yes

**Author** Florian Schwendinger [aut, cre], Dirk Schumacher [aut], Julian Hall [cph], Ivet Galabova [cph], Leona Gottwald [cph], Michael Feldmeier [cph]

**Maintainer** Florian Schwendinger <FlorianSchwendinger@gmx.at>

**Config/pak/sysreqs** cmake pkg-config

**Repository** <https://florianschwendinger.r-universe.dev>

**Date/Publication** 2026-02-08 16:06:36 UTC

**RemoteUrl** <https://github.com/cran/highs>

**RemoteRef** HEAD

**RemoteSha** 1836a57e218ce0a957a13ded16c4be61b2f0cdc6

## Contents

example_model . . . . .	3
example_solver . . . . .	4
hi_model_get_ncons . . . . .	4
hi_model_get_nvars . . . . .	5
hi_model_set_constraint_matrix . . . . .	5
hi_model_set_hessian . . . . .	6
hi_model_set_lhs . . . . .	7
hi_model_set_lower . . . . .	7
hi_model_set_ncol . . . . .	8
hi_model_set_nrow . . . . .	8
hi_model_set_objective . . . . .	9
hi_model_set_offset . . . . .	10
hi_model_set_rhs . . . . .	10
hi_model_set_sense . . . . .	11
hi_model_set_upper . . . . .	11
hi_model_set_vartype . . . . .	12
hi_new_model . . . . .	13
hi_new_solver . . . . .	13
hi_reset_global_scheduler . . . . .	14
hi_solver_add_cols . . . . .	14
hi_solver_add_rows . . . . .	15
hi_solver_add_vars . . . . .	16
hi_solver_change_constraint_bounds . . . . .	16
hi_solver_change_variable_bounds . . . . .	17
hi_solver_clear . . . . .	18
hi_solver_clear_model . . . . .	18
hi_solver_clear_solver . . . . .	19
hi_solver_get_bool_option . . . . .	19
hi_solver_get_constraint_bounds . . . . .	20
hi_solver_get_constraint_matrix . . . . .	20
hi_solver_get_dbl_option . . . . .	21
hi_solver_get_int_option . . . . .	22
hi_solver_get_lp_costs . . . . .	22
hi_solver_get_num_col . . . . .	23
hi_solver_get_num_row . . . . .	23
hi_solver_get_option . . . . .	24
hi_solver_get_options . . . . .	25
hi_solver_get_sense . . . . .	25
hi_solver_get_solution . . . . .	26
hi_solver_get_str_option . . . . .	26
hi_solver_get_variable_bounds . . . . .	27
hi_solver_get_vartype . . . . .	28
hi_solver_infinity . . . . .	28
hi_solver_info . . . . .	29
hi_solver_run . . . . .	29
hi_solver_set_coeff . . . . .	30

hi_solver_set_constraint_bounds . . . . .	30
hi_solver_set_integrality . . . . .	31
hi_solver_set_objective . . . . .	32
hi_solver_set_offset . . . . .	32
hi_solver_set_option . . . . .	33
hi_solver_set_options . . . . .	34
hi_solver_set_sense . . . . .	35
hi_solver_set_variable_bounds . . . . .	35
hi_solver_status . . . . .	36
hi_solver_status_message . . . . .	36
hi_solver_write_basis . . . . .	37
hi_solver_write_model . . . . .	38
highs_available_solver_options . . . . .	38
highs_control . . . . .	39
highs_model . . . . .	39
highs_solve . . . . .	41
highs_solver . . . . .	43
highs_write_model . . . . .	44

<b>Index</b>	<b>45</b>
--------------	-----------

---

example_model	<i>Generate Example Optimization Models</i>
---------------	---

---

## Description

Creates example optimization models for different problem types: - Linear Programming (LP) - Mixed Integer Linear Programming (MILP) - Quadratic Programming (QP)

## Usage

```
example_model(op_type = c("LP", "MILP", "QP"))
```

## Arguments

op_type	Character string specifying the type of optimization model. Must be one of "LP", "MILP", or "QP".
---------	---

## Value

A HiGHS model object configured according to the specified type: - LP: Maximization problem with 3 variables and 3 constraints - MILP: Maximization problem with mixed integer and continuous variables - QP: Problem with quadratic objective function

## Examples

```
model <- example_model("LP")
model <- example_model("MILP")
model <- example_model("QP")
```

example\_solver      *Create a HiGHS Solver Object*

---

**Description**

Creates and solves an example optimization model using the HiGHS solver. This is a convenience wrapper that combines model creation and solving in a single function call.

**Usage**

```
example_solver(op_type = c("LP", "MILP", "QP"))
```

**Arguments**

op\_type      Character string specifying the type of optimization model. Must be one of "LP", "MILP", or "QP".

**Value**

An object of class "highs\_solver".

**Examples**

```
solver <- example_solver("LP")
solver <- example_solver("MILP")
solver <- example_solver("QP")
```

---

hi\_model\_get\_ncons      *Get Number of Constraints in a Model*

---

**Description**

This function retrieves the number of constraints in a given 'highs\_model' object.

**Usage**

```
hi_model_get_ncons(model)
```

**Arguments**

model      A 'highs\_model' object. The model from which to get the number of variables.

**Value**

An integer representing the number of constraints in the model.

**Examples**

```
model <- hi_new_model()
hi_model_get_ncons(model)
```

---

hi\_model\_get\_nvars      *Get Number of Variables in a Highs Model*

---

**Description**

This function retrieves the number of variables in a given Highs model.

**Usage**

```
hi_model_get_nvars(model)
```

**Arguments**

model                    A 'highs\_model' object. The model from which to get the number of variables.

**Value**

An integer representing the number of variables in the model.

**Examples**

```
model <- hi_new_model()
hi_model_get_nvars(model)
```

---

hi\_model\_set\_constraint\_matrix      *Set Constraint Matrix for Highs Model*

---

**Description**

This function sets the constraint matrix for a given Highs model.

**Usage**

```
hi_model_set_constraint_matrix(model, matrix)
```

**Arguments**

model                    an object of class "highs\_model".  
matrix                    a matrix giving the Hessian matrix. Allowed matrix classes are "matrix",  
"dgCMatrix", "matrix.csc", and "simple\_triplet\_matrix".

**Value**

NULL

**Examples**

```
model <- hi_new_model()
matrix <- matrix(c(1, 0, 0, 1), nrow = 2)
hi_model_set_constraint_matrix(model, matrix)
```

---

hi\_model\_set\_hessian *Set Hessian Matrix for Highs Model*

---

**Description**

This function sets the Hessian matrix for a given Highs model.

**Usage**

```
hi_model_set_hessian(model, matrix)
```

**Arguments**

**model** an object of class "highs\_model".

**matrix** a matrix giving the Hessian matrix. Allowed matrix classes are "matrix", "dgCMatrix", "matrix.csc", and "simple\_triplet\_matrix".

**Value**

NULL

**Examples**

```
model <- hi_new_model()
hessian_matrix <- matrix(c(1, 0, 0, 1), nrow = 2)
hi_model_set_hessian(model, hessian_matrix)
```

---

hi_model_set_lhs	<i>Set Left Hand Side for a Highs Model</i>
------------------	---

---

**Description**

This function sets the left hand side for a given Highs model.

**Usage**

```
hi_model_set_lhs(model, lhs)
```

**Arguments**

model	an object of class "highs_model".
lhs	a numeric vector giving the left hand side values.

**Value**

NULL

**Examples**

```
model <- hi_new_model()
model <- hi_model_set_lhs(model, c(0, 1, 2))
```

---

hi_model_set_lower	<i>Set Lower Bounds for Highs Model</i>
--------------------	---

---

**Description**

This function sets the lower bounds for a given Highs model.

**Usage**

```
hi_model_set_lower(model, lower)
```

**Arguments**

model	an object of class "highs_model".
lower	a numeric vector giving the lower bounds.

**Value**

NULL

**Examples**

```
model <- hi_new_model()
lower_bounds <- c(0, 1, 2)
hi_model_set_lower(model, lower_bounds)
```

---

hi\_model\_set\_ncol      *Sets the number of columns in the model*

---

**Description**

This function sets the number of columns in the given model.

**Usage**

```
hi_model_set_ncol(model, ncol)
```

**Arguments**

model                  an object of class "highs\_model".  
ncol                    an integer giving the number of columns (variables) to set in the model

**Value**

NULL

**Examples**

```
model <- hi_new_model()
hi_model_set_ncol(model, 10L) # Sets the model to have 10 columns
```

---

hi\_model\_set\_nrow      *Set the number of rows in the model*

---

**Description**

This function sets the number of rows in the given model.

**Usage**

```
hi_model_set_nrow(model, nrow)
```

**Arguments**

model                  an object of class "highs\_model".  
nrow                    an integer giving the number of rows (variables) to set in the model

**Value**

NULL

**Examples**

```
model <- hi_new_model()
hi_model_set_nrow(model, 5L) # Sets the model to have 5 rows
```

---

hi\_model\_set\_objective

*Set Objective for Highs Model*

---

**Description**

This function sets the objective for a given Highs model.

**Usage**

```
hi_model_set_objective(model, objective)
```

**Arguments**

model            an object of class "highs\_model".  
objective        a numeric vector giving the objective values to be set for the model.

**Value**

NULL

**Examples**

```
model <- hi_new_model()
objective <- c(1, 2, 3)
hi_model_set_objective(model, objective)
```

---

hi\_model\_set\_offset     *Set Offset for Highs Model*

---

**Description**

This function sets the offset for a given Highs model.

**Usage**

```
hi_model_set_offset(model, offset)
```

**Arguments**

model                    an object of class "highs\_model".  
offset                    a numeric value of length 1. The offset value to be set for the model.

**Value**

NULL

**Examples**

```
model <- hi_new_model()  
hi_model_set_offset(model, 10)
```

---

hi\_model\_set\_rhs         *Set Right Hand Side for a Highs Model*

---

**Description**

This function sets the left hand side for a given Highs model.

**Usage**

```
hi_model_set_rhs(model, rhs)
```

**Arguments**

model                    an object of class "highs\_model".  
rhs                       a numeric vector giving the left hand side values.

**Value**

NULL

**Examples**

```
model <- hi_new_model()
model <- hi_model_set_rhs(model, c(0, 1, 2))
```

---

hi\_model\_set\_sense      *Set the sense of the optimization model*

---

**Description**

This function sets the sense of the optimization model to either maximization or minimization.

**Usage**

```
hi_model_set_sense(model, maximum)
```

**Arguments**

model                    an object of class "highs\_model".  
maximum                 a boolean value indicating whether the model should be set to maximization ('TRUE') or minimization ('FALSE').

**Value**

NULL

**Examples**

```
model <- hi_new_model()
hi_model_set_sense(model, TRUE) # Set the model to maximization
hi_model_set_sense(model, FALSE) # Set the model to minimization
```

---

hi\_model\_set\_upper      *Set Upper Bounds for a Highs Model*

---

**Description**

This function sets the upper bounds for a given Highs model.

**Usage**

```
hi_model_set_upper(model, upper)
```

**Arguments**

model            an object of class "highs\_model".  
upper            a numeric vector giving the upper bounds.

**Value**

NULL

**Examples**

```
model <- hi_new_model()
upper_bounds <- c(10, 20, 30)
hi_model_set_upper(model, upper_bounds)
```

---

hi\_model\_set\_vartype    *Set Variable Types in a Highs Model*

---

**Description**

This function sets the variable types in a given Highs model.

**Usage**

```
hi_model_set_vartype(model, types)
```

**Arguments**

model            an object of class "highs\_model".  
types            an integer vector specifying the types of the variables.

**Value**

The function does not return a value. It modifies the 'model' object in place.

**Examples**

```
model <- hi_new_model()
types <- c(1, 2, 1, 0)
hi_model_set_vartype(model, types)
```

---

hi_new_model	<i>Create new Highs Model</i>
--------------	-------------------------------

---

**Description**

Create a new highs model object.

**Usage**

```
hi_new_model()
```

**Value**

an object of class "highs\_model".

**Examples**

```
model <- hi_new_model()
```

---

hi_new_solver	<i>Create a new solver instance.</i>
---------------	--------------------------------------

---

**Description**

This function initializes a new Highs solver instance using the provided model pointer.

**Usage**

```
hi_new_solver(model)
```

**Arguments**

model            an object of class "highs\_model"

**Value**

A new solver instance.

**Examples**

```
model <- example_model()
solver <- hi_new_solver(model)
```

---

 hi\_reset\_global\_scheduler

*Reset Global Scheduler*


---

**Description**

This function resets the global scheduler used by the solver.

**Usage**

```
hi_reset_global_scheduler(blocking)
```

**Arguments**

blocking            A logical value indicating whether to wait for completion.

**Value**

Invisible NULL.

**Examples**

```
hi_reset_global_scheduler(TRUE)
```

---

 hi\_solver\_add\_cols

*Add Variables to Model*


---

**Description**

This function adds new variables (columns) to the optimization model.

**Usage**

```
hi_solver_add_cols(solver, costs, lower, upper, start, index, value)
```

**Arguments**

solver            An object of class "highs\_solver".  
 costs             A numeric vector of objective coefficients.  
 lower             A numeric vector giving the lower bounds of the new variables.  
 upper             A numeric vector giving the upper bounds of the new variables.  
 start             An integer vector of starting positions in the sparse matrix.  
 index             An integer vector of row indices.  
 value             A numeric vector of coefficient values.

**Value**

The solver instance with new variables added.

**Examples**

```
solver <- example_solver()
hi_solver_add_cols(solver, c(1), c(0), c(10), c(0, 1), c(0), c(2))
```

---

hi\_solver\_add\_rows      *Add Constraints to Model*

---

**Description**

This function adds new constraints (rows) to the optimization model.

**Usage**

```
hi_solver_add_rows(solver, lhs, rhs, start, index, value)
```

**Arguments**

solver	An object of class "highs_solver".
lhs	A numeric vector of left-hand side bounds.
rhs	A numeric vector of right-hand side bounds.
start	An integer vector of starting positions in the sparse matrix.
index	An integer vector of column indices.
value	A numeric vector of coefficient values.

**Value**

The solver instance with new constraints added.

**Examples**

```
solver <- example_solver()
hi_solver_add_rows(solver, c(-Inf), c(10), c(0, 2), c(0, 1), c(1, 2))
```

hi\_solver\_add\_vars     *Add Variables to the Solver*

---

**Description**

This function adds new variables to the solver with specified bounds.

**Usage**

```
hi_solver_add_vars(solver, lower, upper)
```

**Arguments**

solver	An object of class "highs_solver".
lower	A numeric vector of lower bounds for the new variables.
upper	A numeric vector of upper bounds for the new variables.

**Value**

The solver instance with the new variables added.

**Examples**

```
solver <- example_solver()
hi_solver_add_vars(solver, lower = c(0, 0, 0), upper = c(10, 10, 10))
```

---

hi\_solver\_change\_constraint\_bounds  
                                  *Change Constraint Bounds*

---

**Description**

This function updates the bounds of an existing constraint in the model.

**Usage**

```
hi_solver_change_constraint_bounds(solver, idx, lhs, rhs)
```

**Arguments**

solver	An object of class "highs_solver".
idx	An integer vector specifying the constraint indices.
lhs	The new left-hand side bound.
rhs	The new right-hand side bound.

**Value**

The solver instance with updated constraint bounds.

**Examples**

```
solver <- example_solver()
hi_solver_change_constraint_bounds(solver, 1, -Inf, 100)
```

---

hi\_solver\_change\_variable\_bounds  
*Change Variable Bounds*

---

**Description**

This function updates the bounds of an existing variable in the model.

**Usage**

```
hi_solver_change_variable_bounds(solver, idx, lower, upper)
```

**Arguments**

solver	An object of class "highs_solver".
idx	An integer specifying the variable index.
lower	The new lower bound.
upper	The new upper bound.

**Value**

The solver instance with updated bounds.

**Examples**

```
solver <- example_solver()
hi_solver_change_variable_bounds(solver, 1, 0, 10)
```

---

hi\_solver\_clear      *Clear All Solver Data*

---

**Description**

This function clears all data from the solver instance, including the model and solution.

**Usage**

```
hi_solver_clear(solver)
```

**Arguments**

solver      An object of class "highs\_solver".

**Value**

The cleared solver instance.

**Examples**

```
solver <- example_solver()
hi_solver_clear(solver)
```

---

hi\_solver\_clear\_model      *Clear Model Data*

---

**Description**

This function clears only the model data from the solver instance.

**Usage**

```
hi_solver_clear_model(solver)
```

**Arguments**

solver      An object of class "highs\_solver".

**Value**

The solver instance with cleared model data.

**Examples**

```
solver <- example_solver()
hi_solver_clear_model(solver)
```

---

hi\_solver\_clear\_solver  
*Clear Solver State*

---

**Description**

This function clears the internal solver state while preserving the model.

**Usage**

```
hi_solver_clear_solver(solver)
```

**Arguments**

solver            An object of class "highs\_solver".

**Value**

The solver instance with cleared solver state.

**Examples**

```
solver <- example_solver()
hi_solver_clear_solver(solver)
```

---

hi\_solver\_get\_bool\_option  
*Get Boolean Option Value*

---

**Description**

This function retrieves the value of a boolean solver option.

**Usage**

```
hi_solver_get_bool_option(solver, key)
```

**Arguments**

solver            An object of class "highs\_solver".  
key                A character string specifying the option name.

**Value**

A logical value.

**Examples**

```
solver <- example_solver()
value <- hi_solver_get_bool_option(solver, "mip_detect_symmetry")
```

---

```
hi_solver_get_constraint_bounds
```

*Get Constraint Bounds*

---

**Description**

This function retrieves the bounds for all constraints in the model.

**Usage**

```
hi_solver_get_constraint_bounds(solver)
```

**Arguments**

`solver` An object of class "highs\_solver".

**Value**

A list containing lower and upper bounds for all constraints.

**Examples**

```
solver <- example_solver()
bounds <- hi_solver_get_constraint_bounds(solver)
```

---

```
hi_solver_get_constraint_matrix
```

*Get Constraint Matrix*

---

**Description**

This function retrieves the constraint matrix of the optimization model.

**Usage**

```
hi_solver_get_constraint_matrix(solver)
```

**Arguments**

`solver` An object of class "highs\_solver".

**Value**

A sparse matrix representing the constraints.

**Examples**

```
solver <- example_solver()
matrix <- hi_solver_get_constraint_matrix(solver)
```

---

hi\_solver\_get\_dbl\_option  
*Get Double Option Value*

---

**Description**

This function retrieves the value of a double precision solver option.

**Usage**

```
hi_solver_get_dbl_option(solver, key)
```

**Arguments**

- solver        An object of class "highs\_solver".
- key            A character string specifying the option name.

**Value**

A numeric value.

**Examples**

```
solver <- example_solver()
value <- hi_solver_get_dbl_option(solver, "time_limit")
```

hi\_solver\_get\_int\_option

*Get Integer Option Value*

---

**Description**

This function retrieves the value of an integer solver option.

**Usage**

```
hi_solver_get_int_option(solver, key)
```

**Arguments**

`solver`            An object of class "highs\_solver".  
`key`                A character string specifying the option name.

**Value**

An integer value.

**Examples**

```
solver <- example_solver()  
value <- hi_solver_get_int_option(solver, "log_dev_level")
```

---

hi\_solver\_get\_lp\_costs

*Get Objective Coefficients*

---

**Description**

This function retrieves the objective coefficients of the linear program.

**Usage**

```
hi_solver_get_lp_costs(solver)
```

**Arguments**

`solver`            An object of class "highs\_solver".

**Value**

A numeric vector of objective coefficients.

**Examples**

```
solver <- example_solver()
costs <- hi_solver_get_lp_costs(solver)
```

---

*hi\_solver\_get\_num\_col* *Get Number of Variables*

---

**Description**

This function returns the number of variables (columns) in the optimization model.

**Usage**

```
hi_solver_get_num_col(solver)
```

**Arguments**

`solver` An object of class "highs\_solver".

**Value**

An integer representing the number of variables.

**Examples**

```
solver <- example_solver()
n_vars <- hi_solver_get_num_col(solver)
```

---

*hi\_solver\_get\_num\_row* *Get Number of Constraints*

---

**Description**

This function returns the number of constraints (rows) in the optimization model.

**Usage**

```
hi_solver_get_num_row(solver)
```

**Arguments**

`solver` An object of class "highs\_solver".

**Value**

An integer representing the number of constraints.

**Examples**

```
solver <- example_solver()
n_constraints <- hi_solver_get_num_row(solver)
```

---

hi\_solver\_get\_option *Get a HiGHS Solver Option*

---

**Description**

Retrieves the value of a specific option from a HiGHS solver instance.

**Usage**

```
hi_solver_get_option(
  solver,
  key,
  type = c("auto", "bool", "integer", "double", "string")
)
```

**Arguments**

solver	A HiGHS solver object of class "highs_solver".
key	A character string specifying the option name to retrieve.
type	Type of the option. Can be one of "auto", "bool", "integer", "double", or "string". When set to "auto" (default), the function will attempt to determine the type from the available options list. Specify a type directly if the option is valid but not listed in the available options.

**Value**

The value of the specified option with the appropriate type.

**Examples**

```
solver <- example_solver()
hi_solver_get_option(solver, "output_flag")
hi_solver_get_option(solver, "solver", type = "string")
```

---

hi\_solver\_get\_options *Get multiple HiGHS Solver Options*

---

**Description**

Retrieves the values of multiple options from a HiGHS solver instance.

**Usage**

```
hi_solver_get_options(solver, keys = NULL)
```

**Arguments**

`solver`            A HiGHS solver object of class "highs\_solver".  
`keys`             A character vector of option names to retrieve.

**Value**

A named list of option values with the appropriate types.

**Examples**

```
solver <- example_solver()  
hi_solver_get_options(solver, c("output_flag", "solver"))
```

---

hi\_solver\_get\_sense *Get the optimization sense of the solver instance.*

---

**Description**

This function returns the optimization sense (e.g., minimization or maximization) of the provided solver instance.

**Usage**

```
hi_solver_get_sense(solver)
```

**Arguments**

`solver`            An object of class "highs\_solver" representing the solver instance.

**Value**

The optimization sense of the solver instance.

**Examples**

```
solver <- example_solver()
hi_solver_get_sense(solver)
```

---

```
hi_solver_get_solution
```

*Get Solution*

---

**Description**

This function retrieves the solution from the solver after optimization.

**Usage**

```
hi_solver_get_solution(solver)
```

**Arguments**

`solver` An object of class "highs\_solver".

**Value**

A list containing the solution information.

**Examples**

```
solver <- example_solver()
hi_solver_run(solver)
solution <- hi_solver_get_solution(solver)
```

---

```
hi_solver_get_str_option
```

*Get String Option Value*

---

**Description**

This function retrieves the value of a string solver option.

**Usage**

```
hi_solver_get_str_option(solver, key)
```

**Arguments**

`solver` An object of class "highs\_solver".  
`key` A character string specifying the option name.

**Value**

A character string.

**Examples**

```
solver <- example_solver()
value <- hi_solver_get_str_option(solver, "solver")
```

---

hi\_solver\_get\_variable\_bounds  
*Get Variable Bounds*

---

**Description**

This function retrieves the bounds for all variables in the model.

**Usage**

```
hi_solver_get_variable_bounds(solver)
```

**Arguments**

`solver` An object of class "highs\_solver".

**Value**

A list containing lower and upper bounds for all variables.

**Examples**

```
solver <- example_solver()
bounds <- hi_solver_get_variable_bounds(solver)
```

---

**hi\_solver\_get\_vartype** *Get Variable Types*

---

**Description**

This function retrieves the type (continuous, integer, etc.) of all variables.

**Usage**

```
hi_solver_get_vartype(solver)
```

**Arguments**

`solver` An object of class "highs\_solver".

**Value**

A character vector of variable types.

**Examples**

```
solver <- example_solver()
types <- hi_solver_get_vartype(solver)
```

---

**hi\_solver\_infinity** *Get Solver Infinity Value*

---

**Description**

This function returns the value that the solver uses to represent infinity.

**Usage**

```
hi_solver_infinity()
```

**Value**

A numeric value representing infinity in the solver.

**Examples**

```
inf <- hi_solver_infinity()
```

---

hi_solver_info	<i>Get Solver Information</i>
----------------	-------------------------------

---

**Description**

This function retrieves detailed information about the solver's state and performance.

**Usage**

```
hi_solver_info(solver)
```

**Arguments**

solver            An object of class "highs\_solver".

**Value**

A list containing solver information.

**Examples**

```
solver <- example_solver()
info <- hi_solver_info(solver)
```

---

hi_solver_run	<i>Run the Solver</i>
---------------	-----------------------

---

**Description**

This function executes the optimization solver on the current model.

**Usage**

```
hi_solver_run(solver)
```

**Arguments**

solver            An object of class "highs\_solver".

**Value**

The solver instance after optimization.

**Examples**

```
solver <- example_solver()
hi_solver_run(solver)
```

hi\_solver\_set\_coeff    *Set a coefficient in the constraint matrix.*

---

**Description**

This function assigns a coefficient value to a specific entry in the constraint matrix.

**Usage**

```
hi_solver_set_coeff(solver, row, col, val)
```

**Arguments**

solver	An object of class "highs_solver".
row	The row index.
col	The column index.
val	The coefficient value.

**Value**

The solver instance with the updated coefficient.

**Examples**

```
solver <- example_solver()
hi_solver_set_coeff(solver, 1, 1, 4.2)
```

---

hi\_solver\_set\_constraint\_bounds  
                          *Set constraint bounds for a given constraint.*

---

**Description**

This function sets the lower and upper bounds for a specific constraint.

**Usage**

```
hi_solver_set_constraint_bounds(solver, index, lower, upper)
```

**Arguments**

solver	An object of class "highs_solver".
index	The constraint index.
lower	The lower bound.
upper	The upper bound.

**Value**

The solver instance with updated constraint bounds.

**Examples**

```
solver <- example_solver()
hi_solver_set_constraint_bounds(solver, 1, -Inf, 100)
```

---

hi\_solver\_set\_integrality

*Set integrality for a set of variables in the solver.*

---

**Description**

This function defines whether a variable is categorized as integral or continuous.

**Usage**

```
hi_solver_set_integrality(solver, index, type)
```

**Arguments**

- solver            An object of class "highs\_solver".
- index            An integer vector specifying the variable index.
- type             An integer vector representing the integrality type.

**Value**

The solver instance with updated integrality settings.

**Examples**

```
solver <- example_solver()
hi_solver_set_integrality(solver, 1, 1)
```

hi\_solver\_set\_objective

*Set the objective coefficient for a set of variables.*

---

### Description

This function assigns a coefficient to a variable in the objective function.

### Usage

```
hi_solver_set_objective(solver, index, coeff)
```

### Arguments

solver	An object of class "highs_solver".
index	The variable index.
coeff	A numeric value representing the objective coefficient.

### Value

The solver instance with the updated objective.

### Examples

```
solver <- example_solver()
hi_solver_set_objective(solver, 2, 3.5)
```

---

hi\_solver\_set\_offset *Set the objective offset for the solver.*

---

### Description

This function sets the objective offset in the solver instance.

### Usage

```
hi_solver_set_offset(solver, ext_offset)
```

### Arguments

solver	An object of class "highs_solver".
ext_offset	A numeric value representing the offset.

**Value**

The solver instance with the updated offset.

**Examples**

```
solver <- example_solver()
hi_solver_set_offset(solver, 5.0)
```

---

hi\_solver\_set\_option    *Set a HiGHS Solver Option*

---

**Description**

Sets the value of a specific option for a HiGHS solver instance.

**Usage**

```
hi_solver_set_option(
  solver,
  key,
  value,
  type = c("auto", "bool", "integer", "double", "string")
)
```

**Arguments**

solver	A HiGHS solver object of class "highs_solver".
key	A character string specifying the option name to set.
value	The value to set for the specified option. Will be coerced to the appropriate type.
type	Type of the option. Can be one of "auto", "bool", "integer", "double", or "string". When set to "auto" (default), the function will attempt to determine the type from the available options list. Specify a type directly if the option is valid but not listed in the available options.

**Value**

Invisibly returns NULL.

**Examples**

```
solver <- example_solver()
hi_solver_set_option(solver, "output_flag", "FALSE")
hi_solver_set_option(solver, "solver", "simplex", type = "string")
```

---

**hi\_solver\_set\_options** *Set Multiple HiGHS Solver Options*

---

**Description**

Sets multiple options for a HiGHS solver instance at once.

**Usage**

```
hi_solver_set_options(solver, control = list())
```

**Arguments**

<code>solver</code>	A HiGHS solver object of class "highs_solver".
<code>control</code>	A named list of options to set. Names should be valid option names and values will be coerced to the appropriate types.

**Value**

Invisibly returns NULL.

**Examples**

```
solver <- example_solver()
hi_solver_set_options(solver, list(output_flag = FALSE, solver = "simplex"))

control <- list(
  presolve = "on",
  solver = "simplex",
  parallel = "on",
  ranging = "off",
  time_limit = 100.0,

  primal_feasibility_tolerance = 1e-7,
  dual_feasibility_tolerance = 1e-7,
  random_seed = 1234,
  threads = 4,

  output_flag = TRUE,
  log_to_console = TRUE,

  run_crossover = "on",
  allow_unbounded_or_infeasible = FALSE,

  mip_detect_symmetry = TRUE,
  mip_max_nodes = 10000,
  mip_max_leaves = 5000,
  mip_feasibility_tolerance = 1e-6
)
hi_solver_set_options(solver, control)
```

---

hi\_solver\_set\_sense    *Set the optimization sense of the solver instance.*

---

**Description**

This function updates the optimization sense for the given solver instance. Use TRUE for maximization and FALSE for minimization.

**Usage**

```
hi_solver_set_sense(solver, maximum)
```

**Arguments**

solver	An object of class "highs_solver".
maximum	A boolean indicating whether to set maximization (TRUE) or minimization (FALSE).

**Value**

The updated solver instance with the new optimization sense.

**Examples**

```
solver <- example_solver()
hi_solver_set_sense(solver, TRUE)
```

---

hi\_solver\_set\_variable\_bounds  
*Set variable bounds for a set of variables.*

---

**Description**

This function sets the lower and upper bounds for a set of variables.

**Usage**

```
hi_solver_set_variable_bounds(solver, index, lower, upper)
```

**Arguments**

solver	An object of class "highs_solver".
index	The variable index.
lower	The lower bound.
upper	The upper bound.

**Value**

The solver instance with updated variable bounds.

**Examples**

```
solver <- example_solver()
hi_solver_set_variable_bounds(solver, 2, 0, 10)
```

---

hi\_solver\_status      *Get Solver Status*

---

**Description**

This function returns the current status of the solver.

**Usage**

```
hi_solver_status(solver)
```

**Arguments**

solver              An object of class "highs\_solver".

**Value**

A status code indicating the solver state.

**Examples**

```
solver <- example_solver()
hi_solver_run(solver)
status <- hi_solver_status(solver)
```

---

hi\_solver\_status\_message  
                          *Get Solver Status Message*

---

**Description**

This function returns a human-readable message describing the current solver status.

**Usage**

```
hi_solver_status_message(solver)
```

**Arguments**

solver            An object of class "highs\_solver".

**Value**

A character string containing the status message.

**Examples**

```
solver <- example_solver()
hi_solver_run(solver)
message <- hi_solver_status_message(solver)
```

---

hi\_solver\_write\_basis    *Write Basis to File*

---

**Description**

This function writes the current basis information to a file.

**Usage**

```
hi_solver_write_basis(solver, filename)
```

**Arguments**

solver            An object of class "highs\_solver".  
filename          A character string specifying the output file path.

**Value**

Invisible NULL.

**Examples**

```
solver <- example_solver()
basis_file <- tempfile(fileext = ".txt")
hi_solver_write_basis(solver, basis_file)
```

hi\_solver\_write\_model *Write Model to File*

---

**Description**

This function writes the current optimization model to a file.

**Usage**

```
hi_solver_write_model(solver, filename)
```

**Arguments**

`solver`            An object of class "highs\_solver".  
`filename`          A character string specifying the output file path.

**Value**

Invisible NULL.

**Examples**

```
solver <- example_solver()
model_file <- tempfile(fileext = ".mps")
hi_solver_write_model(solver, model_file)
```

---

highs\_available\_solver\_options  
*Available Solver Options*

---

**Description**

Reference for the available solver options.

**Usage**

```
highs_available_solver_options()
```

**Value**

A data.frame containing the available solver options.

**Examples**

```
highs_available_solver_options()
```

---

highs_control	<i>Highs Control</i>
---------------	----------------------

---

**Description**

Highs Control

**Usage**

```
highs_control(threads = 1L, time_limit = Inf, log_to_console = FALSE, ...)
```

**Arguments**

`threads` an integer giving the number of threads to be used.  
`time_limit` a double giving the time limit.  
`log_to_console` a logical giving if the output should be shown in the console.  
`...` other arguments supported by the HiGHS solver.

**Examples**

```
control <- highs_control()
```

---

highs_model	<i>Create a Highs Model</i>
-------------	-----------------------------

---

**Description**

Solve linear and quadratic mixed integer optimization problems.

**Usage**

```
highs_model(  
  Q = NULL,  
  L,  
  lower,  
  upper,  
  A = NULL,  
  lhs = NULL,  
  rhs = NULL,  
  types = rep.int(1L, length(L)),  
  maximum = FALSE,  
  offset = 0  
)
```

**Arguments**

Q	a numeric symmetric matrix giving the quadratic part of the objective.
L	a numeric vector giving the linear part of the objective function.
lower	a numeric vector giving the lower bounds of the variables.
upper	a numeric vector giving the upper bounds of the variables.
A	a numeric matrix giving the linear part of the constraints. Rows are constraints, and columns are decision variables.
lhs	a numeric vector giving the left hand-side of the linear constraints.
rhs	a numeric vector giving the right hand-side of the linear constraints.
types	a integer vector or character vector giving the variable types. 'C' or '1' for continuous, 'I' or '2' for integer, 'SC' or '3' for semi continuous, 'SI' or '4' for semi integer and 'II' or '5' for implicit integer.
maximum	a logical if TRUE the solver searches for a maximum, if FALSE the solver searches for a minimum.
offset	a numeric value giving the offset (default is 0).

**Value**

A an object of class `highs_model`.

**Examples**

```
library("highs")
# Minimize:
# x_0 + x_1 + 3
# Subject to:
#           x_1 <= 7
# 5 <= x_0 + 2x_1 <= 15
# 6 <= 3x_0 + 2x_1
# 0 <= x_0 <= 4
# 1 <= x_1
A <- rbind(c(0, 1), c(1, 2), c(3, 2))
m <- highs_model(L = c(1.0, 1), lower = c(0, 1), upper = c(4, Inf),
                 A = A, lhs = c(-Inf, 5, 6), rhs = c(7, 15, Inf),
                 offset = 3)

m

# Minimize:
# -x_2 - 3x_3 + (1/2) * (2 x_1^2 - 2 x_1x_3 + 0.2 x_2^2 + 2 x_3^2)
# Subject to:
# x_1 + x_3 <= 2
# 0 <= x
L <- c(0, -1, -3)
Q <- rbind(c(2, 0.0, -1), c(0, 0.2, 0), c(-1, 0.0, 2))
A <- cbind(1, 0, 1)
m <- highs_model(Q = Q, L = L, lower = 0, A = A, rhs = 2)

m
```

**Description**

Solve linear and quadratic mixed integer optimization problems.

**Usage**

```
highs_solve(
  Q = NULL,
  L,
  lower,
  upper,
  A = NULL,
  lhs = NULL,
  rhs = NULL,
  types = rep.int(1L, length(L)),
  maximum = FALSE,
  offset = 0,
  control = highs_control()
)
```

**Arguments**

Q	a numeric symmetric matrix giving the quadratic part of the objective.
L	a numeric vector giving the linear part of the objective function.
lower	a numeric vector giving the lower bounds of the variables.
upper	a numeric vector giving the upper bounds of the variables.
A	a numeric matrix giving the linear part of the constraints. Rows are constraints, and columns are decision variables.
lhs	a numeric vector giving the left hand-side of the linear constraints.
rhs	a numeric vector giving the right hand-side of the linear constraints.
types	a integer vector or character vector giving the variable types. 'C' or '1' for continuous, 'I' or '2' for integer, 'SC' or '3' for semi continuous, 'SI' or '4' for semi integer and 'II' or '5' for implicit integer.
maximum	a logical if TRUE the solver searches for a maximum, if FALSE the solver searches for a minimum.
offset	a numeric value giving the offset (default is 0).
control	a list giving additional options for the solver, see <a href="#">highs_available_solver_options</a> or the README file for a list of all available options.

**Value**

A list containing the result provided by the solver, containing the following named objects:

<code>primal_solution</code>	a numeric vector giving the primal solution.
<code>objective_value</code>	a numeric giving the objective value.
<code>status</code>	an integer giving the status code
<code>status_message</code>	a character string giving the status message (explanation of the <code>status_code</code> ).
<code>solver_msg</code>	a list giving the original (not canonicalized) solver message.
<code>info</code>	a list giving additional information provided by the solver.

Additional information on can be found in the README file.

**Examples**

```
library("highs")
# Minimize:
#  $x_0 + x_1 + 3$ 
# Subject to:
#  $x_1 \leq 7$ 
#  $5 \leq x_0 + 2x_1 \leq 15$ 
#  $6 \leq 3x_0 + 2x_1$ 
#  $0 \leq x_0 \leq 4$ 
#  $1 \leq x_1$ 
A <- rbind(c(0, 1), c(1, 2), c(3, 2))
s <- highs_solve(L = c(1.0, 1), lower = c(0, 1), upper = c(4, Inf),
                A = A, lhs = c(-Inf, 5, 6), rhs = c(7, 15, Inf),
                offset = 3)
s[["objective_value"]]
s[["primal_solution"]]

# Minimize:
#  $-x_2 - 3x_3 + (1/2) * (2 x_1^2 - 2 x_1x_3 + 0.2 x_2^2 + 2 x_3^2)$ 
# Subject to:
#  $x_1 + x_3 \leq 2$ 
#  $0 \leq x$ 
L <- c(0, -1, -3)
Q <- rbind(c(2, 0.0, -1), c(0, 0.2, 0), c(-1, 0.0, 2))
A <- cbind(1, 0, 1)
s <- highs_solve(Q = Q, L = L, lower = 0, A = A, rhs = 2)
s[["objective_value"]]
s[["primal_solution"]]
```

---

highs_solver	<i>Highs Solver</i>
--------------	---------------------

---

## Description

Create a wrapper around the HiGHS solver. Manly usefull if one wants a low level wrapper around highs with hot-start capabilities.

## Usage

```
highs_solver(model, control = highs_control())
```

## Arguments

model	an object of class "highs_model" created with highs_model().
control	an object of class "highs_control" created with highs_control().

## Details

### Methods

The following methods are provided by the "highs\_solver" class.

- solve(...) method to be called to solve the optimization problem. Returns an integer giving the status code returned by **HiGHS**.
- status() method to obtain the status from the solver.
- status\_message() method to obtain the status message from the solver.
- solution() method to obtain the solution from the solver.
- info() info to obtain additional information from the solver.
- L(i, v) method to get and set the linear part of the objective.
- A(i, j, v) method to get and set the constraint matrix coefficients.
- cbounds(i, lhs, rhs) method to get and set the constraint bounds (left hand-side and right hand-side).
- types(i, v) method to get and set the variable types.
- vbounds(i, lower, upper) method to get and set the variable bounds.
- maximum(maximize) method to get and set the sense of the problem.

### Method arguments

- ... optional control arguments, which can be used to alter the options set via the control argument when initializing the solver.
- i a vector of integers giving the index (vector index or row index) of the coefficients to be altered.

- `j` a vector of integers giving the index (column index) of the coefficients to be altered.
- `v` a vector of doubles giving the values of the coefficients to be altered.
- `lhs` a vector of doubles giving left hand-side.
- `rhs` a vector of doubles giving right hand-side.
- `lower` a vector of doubles giving the lower bounds to be altered.
- `upper` a vector of doubles giving the upper bounds to be altered.

**Value**

an object of class "highs\_solver".

**Examples**

```
A <- rbind(c(0, 1), c(1, 2), c(3, 2))
m <- highs_model(L = c(1.0, 1), lower = c(0, 1), upper = c(4, Inf),
                A = A, lhs = c(-Inf, 5, 6), rhs = c(7, 15, Inf),
                offset = 3)
solver <- highs_solver(m)
```

---

highs\_write\_model      *Write a Highs Model to a File*

---

**Description**

Write an highs model to file.

**Usage**

```
highs_write_model(model, file)
```

**Arguments**

<code>model</code>	an object of class <code>highs_model</code> .
<code>file</code>	a character string giving the filename.

**Examples**

```
model <- example_model()
model_file <- tempfile(fileext = ".mps")
highs_write_model(model, model_file)
```

# Index

example\_model, 3  
example\_solver, 4

hi\_model\_get\_ncons, 4  
hi\_model\_get\_nvars, 5  
hi\_model\_set\_constraint\_matrix, 5  
hi\_model\_set\_hessian, 6  
hi\_model\_set\_lhs, 7  
hi\_model\_set\_lower, 7  
hi\_model\_set\_ncol, 8  
hi\_model\_set\_nrow, 8  
hi\_model\_set\_objective, 9  
hi\_model\_set\_offset, 10  
hi\_model\_set\_rhs, 10  
hi\_model\_set\_sense, 11  
hi\_model\_set\_upper, 11  
hi\_model\_set\_vartype, 12  
hi\_new\_model, 13  
hi\_new\_solver, 13  
hi\_reset\_global\_scheduler, 14  
hi\_solver\_add\_cols, 14  
hi\_solver\_add\_rows, 15  
hi\_solver\_add\_vars, 16  
hi\_solver\_change\_constraint\_bounds, 16  
hi\_solver\_change\_variable\_bounds, 17  
hi\_solver\_clear, 18  
hi\_solver\_clear\_model, 18  
hi\_solver\_clear\_solver, 19  
hi\_solver\_get\_bool\_option, 19  
hi\_solver\_get\_constraint\_bounds, 20  
hi\_solver\_get\_constraint\_matrix, 20  
hi\_solver\_get\_dbl\_option, 21  
hi\_solver\_get\_int\_option, 22  
hi\_solver\_get\_lp\_costs, 22  
hi\_solver\_get\_num\_col, 23  
hi\_solver\_get\_num\_row, 23  
hi\_solver\_get\_option, 24  
hi\_solver\_get\_options, 25  
hi\_solver\_get\_sense, 25  
hi\_solver\_get\_solution, 26  
hi\_solver\_get\_str\_option, 26  
hi\_solver\_get\_variable\_bounds, 27  
hi\_solver\_get\_vartype, 28  
hi\_solver\_infinity, 28  
hi\_solver\_info, 29  
hi\_solver\_run, 29  
hi\_solver\_set\_coeff, 30  
hi\_solver\_set\_constraint\_bounds, 30  
hi\_solver\_set\_integrality, 31  
hi\_solver\_set\_objective, 32  
hi\_solver\_set\_offset, 32  
hi\_solver\_set\_option, 33  
hi\_solver\_set\_options, 34  
hi\_solver\_set\_sense, 35  
hi\_solver\_set\_variable\_bounds, 35  
hi\_solver\_status, 36  
hi\_solver\_status\_message, 36  
hi\_solver\_write\_basis, 37  
hi\_solver\_write\_model, 38  
highs\_available\_solver\_options, 38, 41  
highs\_control, 39  
highs\_model, 39  
highs\_solve, 41  
highs\_solver, 43  
highs\_write\_model, 44